

# Marvin Painted Interior Finish Touchup

## Field Applied Instructions

---

**ABSTRACT:** This instruction demonstrates how to repair small imperfections, nail holes, scratches etc. For procedures on repairing and repainting larger areas, see the Marvin Service Manual or contact your local Marvin representative. The finish coat on painted interior units is a 100% acrylic water based enamel.

### **WARNING!**

Follow all safety, hazard, cleanup, and disposal instructions from the manufacturer of any product used to fill holes, dents, and minor imperfections as well as touch up paint.

---

## Supplies Needed

- Nail hole filler (solvent based is best)
- Touch-up paint: Designer Black (11401919) or White (11401914)
- Paper towels
- 200-400 grit sand paper
- Tack cloth
- Hair dryer

Using a smartphone or similar device, scan this QR code or click [the image below](#) to play a video of this procedure.



---

## *Minor Repairs and Touch Up*

**1. MINOR REPAIRS:** Follow nail hole filler instructions to repair nail holes and small imperfections. Allow to dry. Repairs should be flush or slightly below surface when cured. Sand area lightly with 400 grit sandpaper to feather out edges of existing coating.




Figure 1

**2.** Clean area properly with a tack cloth. Apply paint to the surface of the area with paint applicator. Multiple light coats may be necessary.



Figure 2

**3.** To accelerate drying use a hair dryer on low setting.