Elevate Direct Glaze Round Tops IZ3

| Unit Features | 1 |
|---------------------------------|---|
| Conversions and Certified Sizes | 2 |
| Available Divided Lite Patterns | 3 |
| Section Details: IZ3 Glazing | 4 |



Unit Features

Elevate Direct Glaze Round Top Double Hung IZ3: ELDG RT DH IZ3

For applicable certification and code information, refer to the Introduction and Product Performance chapter.

Frame and Sash:

- The frame exterior is made of ABS, glass reinforced.
- Available colors: Stone White, Pebble Gray, Bronze, Cashmere, Gunmetal, or Ebony.
- The interior is non finger-jointed pine, kiln dried to a moisture content of 6-12% at time of fabrication. Water-repellent, preservative treated.
- Interior wood is available as pine bare wood or factory applied white, clear, or designer black interior finishes.
- Frame width is 4 9/16" (116).
- 4/4 non finger jointed pine interior stop is applied to all units.

Jamb Extension:

- Extension Thickness: 9/16" (14)
- Multiple depths available from 1/8" (3), 1/4"(6), and depths varying between 1/2"(13) and 4"(102) at 1/16" (2) increments
- Maximum jamb depth is 8 9/16". (217)
- 6 13/16" (173) or 6 13/16" (173) jamb extension factory-applied
- All other jamb depth options are available shipped loose.
- Material: Bare Pine
- Option: factory applied white, designer black and clear lacquer interior finish

Installation:


- Factory applied nailing fin.
- Installation clips provided in addition to nailing fin.
- Optional installation brackets for masonry are available in lieu of folding nailing fin.

IZ3 Glazing:

- IZ3 for winds up to 140 miles per hour.
- Glass is laminated insulated Low E2 or E3 Argon, consisting of tempered glass exterior and laminated glass interior.
- The laminated glass is comprised of two pieces of glass with either a SGP or PVB laminate layer between.
- The glazing seal is a silicone bedding on the exterior surface with glazing tape on the interior.

Interior / Exterior Simulated Divided Lites (SDL):

- Interior bar: 7/8" (22) wide bars
- Pine bare wood or factory applied white, clear, or designer black finishes to match the interior.
- Exterior straight bar: 7/8" (22) wide bars Ultrex, finish to match exterior
- Exterior radius bar: ABS Hi, HDDB 7/8" (22) wide bars. Finish to match exterior.



NOTE: Drawings on this page are not to scale.


Conversions and Certified Sizes

| Unit Measurement | Width | | | | |
|------------------|--------------------------------------|---------|-------|---------|-------|
| From | То | Widtr | | Height | |
| Rough Opening | | in | mm | in | mm |
| Masonry Opening | Rough Opening (RT1, RT2, RT6, RT7/8) | + 1/2 | (13) | + 1/4 | (6) |
| Masonry Opening | Rough Opening (RT27 - circle) | + 1/2 | (13) | + 1/2 | (13) |
| OM of Frame | Rough Opening (RT1, RT2, RT6, RT7/8) | + 1 | (25) | + 1/2 | (13) |
| OM of Frame | Rough Opening (RT27 - circle) | + 1 | (25) | + 1 | (25) |
| Daylight Opening | Rough Opening (RT1, RT2, RT6, RT7/8) | + 5 | (127) | + 4 1/2 | (114) |
| Daylight Opening | Rough Opening (RT27 - circle) | + 5 | (127) | + 5 | (127) |
| Frame | in | mm | in | mm | |
| Daylight Opening | OM of Frame (RT1, RT2, RT6, RT7/8) | + 4 | (102) | + 4 | (102) |
| Daylight Opening | OM of Frame (RT27 - circle) | + 4 | (102) | + 4 | (102) |
| Glass | in | mm | in | mm | |
| OM of Frame | Glass (RT1, RT2, RT6, RT7/8) | -3 1/16 | (78) | -3 1/16 | (78) |
| OM of Frame | Glass (RT27-circle) | -3 1/16 | (78) | -3 1/16 | (78) |
| Daylight Opening | Glass (RT1, RT2, RT6, RT7/8) | +15/16 | (24) | +15/16 | (24) |
| Daylight Opening | Glass (RT27-circle) | +15/16 | (24) | +15/16 | (24) |

| Product | Air Tested to psf | Water Tested to psf | Certification Rating | Design Pressure | Max Overall FrameWidth | | Max Overall FrameHeight | |
|---------------------------------|----------------------|------------------------|-------------------------|--------------------|------------------------------|--------|-------------------------------|--------|
| | | | | | in | mm | in | mm |
| Casement Round Top IZ3 | 1.57 | 8.35 | LC-PG55-FW | + 55 / - 65 | 83 1/8 | (2111) | 83 1/8 | (2111) |
| Casement Round Top IZ3 | 1.57 | 8.35 | LC-PG55-FW | + 55 / - 65 | 72 1/16 | (1830) | 29 9/16 | (751) |
| Double Hung Round Top IZ3 | 1.57 | 8.35 | LC-PG55-FW | + 55 / - 65 | 83 1/8 | (2111) | 83 1/8 | (2111) |
| Double Hung Round Top IZ3 | 1.57 | 8.35 | LC-PG55-FW | + 55 / - 65 | 71 1/16 | (1805) | 29 9/16 | (751) |



Available Divided Lite Patterns



Divided Lite Options

NOTES:


- SDL interior bars are available bare, or with a white, clear, or designer black interior finish. The SDL exterior finish will be determined by the unit exterior finish.
- White, clear, and designer black interior finishes on SDLs, and Interior Trim is available at no additional charge.
- White, Clear, and Designer Black interior finishes on Jamb Extensions are available at no additional cost when they match the interior finish of the window. White Jamb Extensions on a unit with a Designer Black interior are available at an additional cost.



Section Details: IZ3 Glazing

Scale: 3" = 1' 0"

Casement



Double Hung

