

Sliding Door Automatic Control Device

Installation Instructions

ABSTRACT: Use this site prep guide in conjunction with the Sliding Door Automatic Control Site Prep Instruction. Install the door prior to installing the motor. The following instructions assume the installer has prior product and installation training before attempting to install the device.

IMPORTANT

The motor and control box are complete units and must not be disassembled in the field.

Table of Contents

Tools Needed	1	Modern Multi-Slide Door Connections	11
Door/Stud/Motor Cavity Prep	2	Threading the Belt.....	14
Wiring Prep	3	Installing the Optional Closing Ramp	18
Install the Pulley Corner Key.....	4	Optional Belt Clips.....	19
Install the Motor	5	Programming.....	20
Install the Control Box.....	7	Reprogramming	21
Connecting Components	9		

Tools Needed

- 14 gauge cable crimper
- Wire stripper
- Power drill/driver
- 1 1/4" drill bit
- 7/64" drill bit
- 9/64" Allen Wrench
- 3/32" Allen wrench
- Measuring tape
- Heavy duty shear (for cutting the belt)
- Extended #2 Phillips bit
- Safety glasses

WARNING!

Always practice safety! Wear the appropriate eye, ear, and hand protection, especially when working with power tools.

Door/Stud/Motor Cavity Prep

There are two options to consider when prepping the stud cavity to accept the drive belt.

- 1. Option A: Drill into the stud adjacent to the interior most track of the door with a 1 1/4" hole saw. See [Figure 1](#).




Figure 1

1	1 3/4" on center lined up with the corner key.
---	--

- 2. Option B: Measure the height of your door and cut a 1 1/4" x 2 1/2" deep notch lined up with the belt pass-through on the corner key. When installation is complete cover the notch with a steel tie plate. See [Figure 2](#).




Figure 2 Notched stud

1	Steel stud tie
2	Notch

Install the Pulley Corner Key

1. On ultimate MSD only: Remove the cover with a 9/64" Allen wrench. See Figure 3. Remove the bottom washer, the pulley and top washer and set aside. See Figure 4. This will give you access to the side screw holes. Attach the pulley base with two #8 x 3" screws into the side RO. See Figure 5. Replace the washers, pulley and cover in the reverse order you removed them.




Figure 3




Figure 4



Figure 5

2. Make sure the corners are properly shimmed near the corners to support the corner key pulley fasteners.

3. Fasten the pulley corner key into the head jamb rough opening with two #8 x 3" screws. provided. See Figure 6.




Figure 6

1	#8 x 3" screws
---	----------------

Install the Motor

IMPORTANT

Check the door for proper operation before proceeding. Make the sure the panels are square and operating smoothly. Make sure you have proper head jamb clearance above the panels for the belt to travel. Make sure the locking hardware locks and engages properly.



Hint

You will align the motor so it is centered on the lead panel. Mark a centerline in the motor cavity to aid installation. The front of the motor is the side with one stand-off at the top of the motor.

1. Install a screw on their centerline within 3" of the stud and leave the head proud about 3/4"-1".



Figure 7

2. Hang the motor by the slotted hole on the front edge of the mounting plate. See Figure 8.



Figure 8

3. Pre-drill with a 7/64" drill bit and fasten the four corners with #8x 3" screws provided

4. Set the motor drive pulley in line with the belt holes and secure the two set screws with a 3/32" Allen wrench. Adjust the pulley up or down until aligned. Then tighten the set screws. This pulley can be adjusted later to avoid belt rub.

IMPORTANT

Make sure there is clearance below the drive pulley. (Note the area marked with a red arrow in [Figure 9](#) (next page)).




Figure 9 Drive pulley shown with belt attached

1	Set screws (2) are located at 90 degrees from each other
---	--

Install the Control Box

The control box can be located within 100' of the motor. Use an accessible, well lit location in an A/V closet or utility room separate from the motor cavity. Mount the control box chest high in a well lit space.

1. On the front of the control box, make sure the AC and Battery switches are in the off position. See Figure 10.



Figure 10

2. Mount the box from the side or back using the installation keyholes on the control box and the installation screws provided. Use an extended #2 Phillips bit to aid in installation. When mounting on the back start with the bottom left screw first. Fasten all screws to securely mount the control box (4 screws for rear mount, 2 screws for side mount). See Figure 11.




Figure 11 Rear mounting holes. Controller removed for illustrative purposes only.

3. Determine which knockouts to remove to allow power and CAT5e cables to enter the control box.

IMPORTANT

Make sure you leave some slack in the cables before connecting to the control box. Make sure there are no tight bends in any cable.




Figure 12

1	Knockouts
---	-----------

4. Pass the cables through the knockout and connect to the correct receiver. Make the following connections in the control box:

- Connect the white 14 gauge wire to the A1 port and the black 14 gauge wire to the A2 port.
- Connect the red CAT5e supercable to the corresponding connectors from the motor.
- Connect the yellow CAT5e cable to the yellow port on the motor.
- Connect the blue CAT5e cable to the blue port on the control box or motor, whichever is more accessible.




Figure 13 Control Box connections.

1	A1 and A2 ports--14 gauge wires from motor
2	Red CAT5e from motor
3	Blue CAT 5e (can be connected to control box or motor)

5. Remove the battery cover and battery from the control box. Connect the two loose red battery cables together to complete the circuit. Replace the battery and battery cover/nut. See Figure 14 and Figure 15.




Figure 14

1	Battery cover nut
---	-------------------




Figure 15

1	Battery cables.
---	-----------------

6. Insert the AC power cord into the bottom of the control box and plug the other end into a standard 110v/ 15 amp dedicated circuit.

ATTENTION

The [next step](#) on hard wiring should only be done by a licensed electrician.

7. **Optional Hardwire:** Remove the two screws from the power port on the control box to access internal wiring.

Connecting Components

1. Attach the blue female cable crimp connectors to the 14-2 cable from the control box. [See Figure 16.](#)




Figure 16

2. **Control Box to Motor:** the red Super Cable connects to the corresponding port on the motor. Red and black female leads from the motor to the black and white male leads from the control box. [See Figure 17.](#)




Figure 17

1	Ensure a solid crimp
---	----------------------

3. **Wall Switches:** Connect the blue CAT5e from the "out" port on the wall switch to the corresponding wall switch port on the motor or control box. Additional wall switches can be added to the "in" port on the wall switch (daisy chain).




Figure 18

1	Wall switch "out" port.
---	-------------------------

4. **Sensors:** connect the yellow CAT5e to the corresponding sensor port on the motor. See [Figure 18](#) and [Figure 19](#).




Figure 19

1	Wall switch port on the motor
2	Sensor ports on the motor

5. Use double sided tape to attach to the sensor to the head jamb cover. The sensor eye will fit through the hole in the cover. See [Figure 20](#).



Figure 20 Inset shows sensor eye through head jamb cover

1	Sensor through head jamb cover
---	--------------------------------

Modern Multi-Slide Door Connections

1. Connect the "Wall Switch" port on the motor and the "Motor" port on the Marvin Control Module with the 2 ft. Cat5E cable.




Figure 21

2. Connect the wall switch to the "Wall Switch" port on the module and NOT the motor. Optionally, an additional port is available in the control box.

NOTE: The Modern Multi-Slide door uses a power transfer device (PTD) on the panel and in the frame. The PTD on the panel is installed at the factory. Take caution not to bend the springs when installing the panel.

3. Install the frame PTD in the head jamb prior to panel installation. First, label your wire bundles. Label the reed switch bundle as "closed". Label the leaf spring bundle as "lock".




Figure 22 Label the reed switch and leaf spring wire bundles.

ATTENTION

Run PTD wires through the frame fabrication and into the RO prior to completing the installation (before any insulation is applied).

4. If necessary (as in bi-parting configurations) splice the **un-stripped** wires with the connectors included and re-label the ends as "Closed" and "Lock".

IMPORTANT

Do not strip the wires when using the connectors. If the wires are stripped, trim the exposed wire back. The orange button on the connector must be flush to the housing when compressed.




Figure 23

5. Shim the frame at the frame PTD location take care not to bow the head jamb.




Figure 24

6. Install the frame PTD with #10 x 3" screws provided. Center the screws in the slots to position the PTD initially. When the PTD is positioned where you want it, drive the screws into the RO framing. **DO NOT OVERTIGHTEN SCREWS**




Figure 25

NOTE: If adjustment is needed after installation, loosen the screws and slide the PTD left/right then tighten.

7. Remove the black 2 pin connector marked "Close Sensor" and the green 2 pin connector marked "Lock Sensor" from the control module.




Figure 26

8. Connect the "closed" wire to the screw terminal on the black "Close Sensor". Connect the "locked" wire to the screw terminal on the green 2 pin connector marked "Lock Sensor". Re-install the black and green 2 pin connectors on the control module.

If you are on-boarding the unit to your Wi-fi network, refer to the [User and Troubleshooting Guide](#).




Figure 27

Threading the Belt

IMPORTANT

Ensure there are no twists in the belt throughout installation.

1. Loosen turnbuckle until there are 5 threads of engagement on each side. [See Figure 28](#)




Figure 28

2. Insert belt through belt clamp. [See Figure 29](#)



Figure 29

3. Attach belt on panel bracket and fasten with #8- 32 x 3/8" screw. [See Figure 30](#), [Figure 31](#), and [Figure 32](#).




Figure 30




Figure 31

4. Thread belt through exterior side of return pulley. Ensuring no twists in belt, thread belt over top of panel with teeth facing up. [See Figure 32](#)



Figure 32

IMPORTANT

On bi-parting units, belt must run above the structural bracket with teeth facing up. [See Figure 33.](#)



Figure 33

1	Structural bracket
---	--------------------

5. Thread the belt through the pass through corner key and around motor drive sprocket. Continue to thread the belt back over the panel tooth side up. [See Figure 34](#)



Tip

Ensure that termination of the belt is on the exterior side of the door.




Figure 34

1	Holes in stud to access corner key
2	Belt

6. Pull the belt tight against the turnbuckle. Mark the belt to ensure there are 3 teeth of engagement on the turnbuckle. Cut the belt with a heavy shear. [See Figure 35.](#)




Figure 35

1	Cut next to the "tooth"
2	End tooth is fully engaged with clamp

7. Fasten belt to turnbuckle, completing the loop. See Figure 36.




Figure 36

1	Turnbuckle
2	Belt
3	Clip




Figure 37

1	Turnbuckle
2	Set screws

8. Tighten turnbuckle nut until belt is taut, ensuring turnbuckle ends don't spin (twisting belt).

9. Tighten the lock nut against the turnbuckle barrel. See Figure 38.




Figure 38

1	Barrel
2	Lock nut

10. Fasten the turnbuckle to the pulley side of the panel with two screws. [See Figure 39](#)



Figure 39

NOTE: Follow the [next step](#) and [step 12 on page 17](#) for Bi-Parting units only.

11. Hook the bi-parting clamp on the interior side of the belt with the teeth facing upwards. [See Figure 40](#)



Figure 40

12. With panels in locked position, slide the clamp into the route and fasten with two screws. Ensure the clamp is engaged with the teeth on the belt. [See Figure 41](#)



Figure 41

Installing the Optional Closing Ramp

Using a smartphone or similar device, scan the QR code or click [here](#) to play a video of this procedure.



NOTE: the closing ramp is mounted to the frame, and helps apply force to the back side of the panel to ensure the panel fully seats into the jamb. It is typically needed on narrow and tall panels.

1. Fully close the door.
2. Locate the pre-drilled hole 1" behind the interlocking stile. [See Figure 42.](#)



Figure 42

3. Open the primary panel(s) past 1 full panel width.

NOTE: If you have an OX, XO, or OX-XO unit, leave the panel(s) fully closed.

4. Install the closing ramp, using the provided #8 x 3" screw, into the pre-drilled hole.
5. Close and lock the door.
6. Pull the ramp tight so that it fully contacts the turnbuckle. [See Figure 43.](#)




Figure 43

NOTE: If more contact is needed, adjust the set screw in the closing ramp.

7. Open and close the door using Sliding Door Automatic Control System. Ensure the door manually locks. If the door doesn't manually lock, adjust the set screw. [See Figure 44.](#)




Figure 44

Optional Belt Clips

1. On large units, the belt clips can be installed to eliminate belt sag. Use the belt clip to hold the belt **(opposite of the turnbuckle or bi-parting bracket)** with teeth up against the head track. Fasten the belt clip in the head track with the screws provided. Pre-drilling may be necessary. [See Figure 45.](#)




Figure 45

1	Belt clip
---	-----------

Programming

NOTE: Summit will provide documentation on how to properly program the system.

- 1. Initial Programming:** make sure both AC and DC power to the system are turned off on the control box cover. Place the lead panels to the halfway point of the opening. Then turn on both AC and DC power.
2. Press the "OPEN" button on the wall switch. The panel will start to move. If the door is moving to the open position, the polarity is correct. Let the panel move 24" and then press "UNLOCK" on the wall switch. The door will stop. [See Figure 46.](#)




Figure 46

3. If the polarity is incorrect and the door is closing, press "OPEN" a second time and the door will change polarity. Let the panel travel approximately 24" before pressing "UNLOCK" and moving on to the next step.
4. Manually move the door to the fully open position. Press and hold the "UNLOCK" button until the touch screen shows "Release Button!" or red and blue lights blink rapidly (on non-touch screens). [See Figure 47.](#)




Figure 47

5. Move the door manually to the fully closed position. Press and hold the "UNLOCK" button until the touch screen shows "Release Button!" or red and blue lights blink rapidly (on non-touch screens). [See Figure 48.](#)




Figure 48

6. Once the "UNLOCK" button is released, the door will automatically cycle in programming mode.

WARNING!

The automatic stop feature is disabled in programming mode. Make sure the opening is kept clear when programming.

7. Once the door stops and is engaged in the closed position, the programming is complete.

Reprogramming

In the event that you replace a panel, experiencing problems with door motorization, run these steps to re-program/reset.

1. With both AC and Battery power off on the control box cover, place the lead panel to the halfway point of the opening.
2. Open the control box and flip dip switch 8 to the right.
[See Figure 49.](#)




Figure 49

1	Dipswitch 8
---	-------------

3. Turn on both AC and Battery power switches on the control box cover. Open the control box and flip dip switch 8 back to the left. [See Figure 50.](#)




Figure 50

1	Dipswitch 8
---	-------------

4. Refer to [Programming on page 20.](#)